KERN RIB10K-3HM

High-quality retail scale with large item memory and user-friendly concept of operation





Measuring system	
Adjustment options:	External calibration
Eccentric loading at 1/3 [Max]:	2g 5g
Linearity:	2g 5g
Number of weighing ranges:	2
Readability [d]:	2g 5g
Recommended adjusting weight:	10 kg (M1); 5 kg (M1)
Repeatability:	2g 5g
Resolution:	3 3.000
Stabilisation time under laboratory conditions:	2 s
Tare range:	15 kg
Warm up time:	10 min 10 min
Weighing capacity [Max]:	6 kg 15 kg
Weighing system:	Strain gauge
Weighing units:	kg

Display	
Additional Display possible:	yes
Display digit height (large):	1,800 cm

Technical data about verification		
Minimum load [Min]:	40 g 100 g	
Periodic Verification for Italy:	969-112	
Verification approval conforming to 2014/31/EU:	yes	
Verification by KERN possible:	yes	
Verification class:	III	
Verification value [e]:	2g 5g	

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %

Power supply	
Battery:	no battery
Charging time:	14 h
Input voltage:	100V-240V AC 50/60Hz 0,400 Amax
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	UK EURO CH
Operating time (Backlight off):	80 h
Operating time (Backlight on):	40 h
Rechargeable battery:	Rchrg. battery optional - intern

eer viees (optional)	
Adjustment at the location of instal	llation: 961-248
DAkkS Certificate:	963-128
Verification:	965-228
Category	
Brand:	KERN
Category:	Balances
Product Group:	Price computing scale
Packaging & shipping	

Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	450 x 400 x 210 mm
Gross weight:	5,500 kg
Net weight:	3,800 kg
Shipping method:	Parcel service


Construction	
Casing material:	Plastic
Dimensions housing (WxDxH):	325 x 340 x 115 mm
of stand:	40,500 cm
Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted (WxDxH):	325 x 340 x 405 mm
Revolving screw feet:	yes
Weighing surface (WxD):	294 x 225 mm

KERN RIB 10K-3HM



High-quality retail scale with large item memory and user-friendly concept of operation

KERN RIB 10K-3M







Measuring system	
Adjustment options:	External calibration
Eccentric loading at 1/3 [Max]:	2g 5g
Linearity:	2g 5g
Number of weighing ranges:	2
Readability [d]:	2g 5g
Recommended adjusting weight:	10 kg (M1); 5 kg (M1)
Repeatability:	2g 5g
Resolution:	3 3.000
Stabilisation time under laboratory conditions:	2 s
Tare range:	15 kg
Warm up time:	10 min 10 min
Weighing capacity [Max]:	6 kg 15 kg
Weighing system:	Strain gauge
Weighing units:	kg

Display	
Additional Display possible:	yes
Display digit height (large):	1,800 cm

Technical data about verification		
Minimum load [Min]:	40 g 100 g	
Periodic Verification for Italy:	969-112	
Verification approval conforming to 2014/31/EU:	yes	
Verification by KERN possible:	yes	
Verification class:	III	
Verification value [e]:	2g 5g	

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %

Power supply	
Battery:	no battery
Charging time:	14 h
Input voltage:	100V-240V AC 50/60Hz 0,400 Amax
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	UK EURO CH
Operating time (Backlight off):	80 h
Operating time (Backlight on):	40 h
Rechargeable battery:	Rchrg. battery optional - intern

Adjustment at the location of installation: 961-248	
DAkkS Certificate:	963-128
Verification:	965-228
Category	
Brand:	KERN
Category:	Balances
Product Group:	Price computing scale

Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	380 x 380 x 155 mm
Gross weight:	4,500 kg
Net weight:	3,200 kg
Shipping method:	Parcel service


Construction	
Casing material:	Plastic
Dimensions housing (WxDxH):	325 x 340 x 115 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted (WxDxH):	325 x 340 x 115 mm
Revolving screw feet:	yes
Weighing surface (WxD):	294 x 225 mm

KERN RIB 10K-3M



High-quality retail scale with large item memory and user-friendly concept of operation

KERN RIB30K-2HM







Measuring system	
Adjustment options:	External calibration
Eccentric loading at 1/3 [Max]:	5 g 10 g
Linearity:	5 g 10 g
Number of weighing ranges:	2
Readability [d]:	5 g 10 g
Recommended adjusting weight:	30 kg (M1)
Repeatability:	5 g 10 g
Resolution:	3 3.000
Stabilisation time under laboratory conditions:	2 s
Tare range:	30 kg
Warm up time:	10 min 10 min
Weighing capacity [Max]:	15 kg 30 kg
Weighing system:	Strain gauge
Weighing units:	kg

Display	
Additional Display possible:	yes
Display digit height (large):	1,800 cm

Technical data about verification		
Minimum load [Min]:	100 g 200 g	
Periodic Verification for Italy:	969-112	
Verification approval conforming to 2014/31/EU:	yes	
Verification by KERN possible:	yes	
Verification class:	III	
Verification value [e]:	5 g 10 g	

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %

Power supply	
Battery:	no battery
Charging time:	14 h
Input voltage:	100V-240V AC 50/60Hz 0,400 Amax
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	UK EURO CH
Operating time (Backlight off):	80 h
Operating time (Backlight on):	40 h
Rechargeable battery:	Rchrg. battery optional - intern

Services (optional)		
Adjustment at the location of installation: 961-248		
DAkkS Certificate:	963-128	
Verification:	965-228	
Category		
Brand:	KERN	
Category:	Balances	
Product Group:	Price computing scale	

Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	450 x 400 x 210 mm
Gross weight:	5,500 kg
Net weight:	3,800 kg
Shipping method:	Parcel service


Construction	
Casing material:	Plastic
Dimensions housing (WxDxH):	325 x 340 x 115 mm
of stand:	40,500 cm
Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted (WxDxH):	325 x 340 x 405 mm
Revolving screw feet:	yes
Weighing surface (WxD):	294 x 225 mm

KERN RIB30K-2HM



High-quality retail scale with large item memory and user-friendly concept of operation

KERN RIB 30K-2M







Measuring system	
Adjustment options:	External calibration
Eccentric loading at 1/3 [Max]:	5 g 10 g
Linearity:	5 g 10 g
Number of weighing ranges:	2
Readability [d]:	5 g 10 g
Recommended adjusting weight:	30 kg (M1)
Repeatability:	5 g 10 g
Resolution:	3 3.000
Stabilisation time under laboratory conditions:	2 s
Tare range:	30 kg
Warm up time:	10 min 10 min
Weighing capacity [Max]:	15 kg 30 kg
Weighing system:	Strain gauge
Weighing units:	kg

Display	
Additional Display possible:	yes
Display digit height (large):	1,800 cm

Technical data about verification	
Minimum load [Min]:	100 g 200 g
Periodic Verification for Italy:	969-112
Verification approval conforming to 2014/31/EU:	yes
Verification by KERN possible:	yes
Verification class:	III
Verification value [e]:	5 g 10 g

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %

Power supply	
Battery:	no battery
Charging time:	14 h
Input voltage:	100V-240V AC 50/60Hz 0,400 Amax
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	UK EURO CH
Operating time (Backlight off):	80 h
Operating time (Backlight on):	40 h
Rechargeable battery:	Rchrg. battery optional - intern

Colvidos (optional)		
Adjustment at the location of in	nstallation: 961-248	
DAkkS Certificate:	963-128	
Verification:	965-228	

Category	
Brand:	KERN
Category:	Balances
Product Group:	Price computing scale

Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	380 x 380 x 155 mm
Gross weight:	4,500 kg
Net weight:	3,200 kg
Shipping method:	Parcel service


Construction	
Casing material:	Plastic
Dimensions housing (WxDxH):	325 x 340 x 115 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted (WxDxH):	325 x 340 x 115 mm
Revolving screw feet:	yes
Weighing surface (WxD):	294 x 225 mm

KERN RIB30K-2M



High-quality retail scale with large item memory and user-friendly concept of operation

KERN RIB6K-3HM







Measuring system	
Adjustment options:	External calibration
Eccentric loading at 1/3 [Max]:	5 g 10 g
Linearity:	1 g 2 g
Number of weighing ranges:	2
Readability [d]:	1g 2g
Recommended adjusting weight:	5 kg (F2); 1 kg (F2)
Repeatability:	1g 2g
Resolution:	3 3.000
Stabilisation time under laboratory conditions:	2 \$
Tare range:	6 kg
Warm up time:	10 min 10 min
Weighing capacity [Max]:	3 kg 6 kg
Weighing system:	Strain gauge
Weighing units:	kg

Display	
Additional Display possible:	yes
Display digit height (large):	1,800 cm

Technical data about verification	
Minimum load [Min]:	20 g 40 g
Periodic Verification for Italy:	969-112
Verification approval conforming to 2014/31/EU:	yes
Verification by KERN possible:	yes
Verification class:	III
Verification value [e]:	1 g 2 g

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %

Power supply	
Battery:	no battery
Charging time:	14 h
Input voltage:	100V-240V AC 50/60Hz 0,400 Amax
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	UK EURO CH
Operating time (Backlight off):	80 h
Operating time (Backlight on):	40 h
Rechargeable battery:	Rchrg. battery optional - intern

Services (optional)		
Adjustment at the location of installation: 961-248		
DAkkS Certificate:	963-128	
Verification:	965-228	
Category		

Brand:	KERN
Category:	Balances
Product Group:	Price computing scale

Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	450 x 400 x 210 mm
Gross weight:	5,500 kg
Net weight:	3,800 kg
Shipping method:	Parcel service

Construction	
Casing material:	Plastic
Dimensions housing (WxDxH):	325 x 340 x 115 mm
of stand:	40,500 cm
Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted (WxDxH):	325 x 340 x 405 mm
Revolving screw feet:	yes
Weighing surface (WxD):	294 x 225 mm

KERN RIB6K-3HM



High-quality retail scale with large item memory and user-friendly concept of operation

KERN RIB6K-3M

High-quality retail scale with large item memory and user-friendly concept of operation





Measuring system	
Adjustment options:	External calibration
Eccentric loading at 1/3 [Max]:	5 g 10 g
Linearity:	1 g 2 g
Number of weighing ranges:	2
Readability [d]:	1 g 2 g
Recommended adjusting weight:	5 kg (F2); 1 kg (F2)
Repeatability:	1 g 2 g
Resolution:	3 3.000
Stabilisation time under laboratory conditions:	2 s
Tare range:	6 kg
Warm up time:	10 min 10 min
Weighing capacity [Max]:	3 kg 6 kg
Weighing system:	Strain gauge
Weighing units:	kg

Display	
Additional Display possible:	yes
Display digit height (large):	1,800 cm

Technical data about verification	
Minimum load [Min]:	20 g 40 g
Periodic Verification for Italy:	969-112
Verification approval conforming to 2014/31/EU:	yes
Verification by KERN possible:	yes
Verification class:	III
Verification value [e]:	1 g 2 g

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %

Power supply	
Battery:	no battery
Charging time:	14 h
Input voltage:	100V-240V AC 50/60Hz 0,400 Amax
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	UK EURO CH
Operating time (Backlight off):	80 h
Operating time (Backlight on):	40 h
Rechargeable battery:	Rchrg. battery optional - intern

(- /		
Adjustment at the location of installation: 961-248		
DAkkS Certificate:	963-128	
Verification:	965-228	
Catagory	_	

Category	
Brand:	KERN
Category:	Balances
Product Group:	Price computing scale

Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	380 x 380 x 155 mm
Gross weight:	4,500 kg
Net weight:	3,200 kg
Shipping method:	Parcel service

Construction	
Casing material:	Plastic
Dimensions housing (WxDxH):	325 x 340 x 115 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted (WxDxH):	325 x 340 x 115 mm
Revolving screw feet:	yes
Weighing surface (WxD):	294 x 225 mm

KERN RIB6K-3M



High-quality retail scale with large item memory and user-friendly concept of operation

Piktogramme STANDARD Lacut Memory Unit 230 V DMS 1 DAY OPTION DAKKS ACCU +3 DAYS FACTORY