KERN UFB1.5T0.5M

Pallet scale with steel load support (IP67) and EC type approval [M]





Measuring system	
Adjustment options:	External calibration
Eccentric loading at 1/3 [Max]:	1 kg
Linearity:	1 kg
Load cell connection:	4-wire
Readability [d]:	500 g
Recommended adjusting weight:	1500 kg (M2)
Repeatability:	500 g
Resolution:	3000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-1,500 t
Warm up time:	10 min
Weighing capacity [Max]:	1,500 t
Weighing system:	Strain gauge
Weighing units:	kg

Display		
Display digit height (large):	5,200 cm	

Technical data about verification	
Minimum load [Min]:	10 kg
Periodic Verification for Italy:	969-112
Verification approval conforming to 2014/31/EU:	yes
Verification by KERN possible:	yes
Verification class:	III
Verification value [e]:	500 g

Functions		
Counting function:	yes	
Function to save totals:	yes	
Vibration-free weighing (Animal weighing program):	yes	
Weighing with tolerance range:	yes	

Environmental conditions	
Maximum humidity:	95 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	10 %
Minimum humidity:	10 %

Power supply	
Battery:	no battery
Charging time:	12 h
Input voltage:	100 V - 240 V 50 / 60 Hz
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	EURO CH UK
Operating time (Backlight off):	35 h
Operating time (Backlight on):	8 h
Rechargeable battery:	Rchrg. battery optional (factory)

Services (optional)		
Adjustment at the location of ins	stallation: 961-250	
DAkkS Certificate:	963-130	
Verification:	965-230	

Category	
Brand:	KERN
Category:	Balances
Product Group:	Pallet scale

i Toddict Group.	i aliet scale
Packaging & shipping	
Delivery:	48 h
Dimensions packaging (WxDxH):	1400 x 875 x 300 mm
Gross weight:	81 kg
Net weight:	51 kg
Shipping method:	Freight forwarder
Construction	
Cable length:	5 m
Cable length of display device:	5 m
Dimensions of display device	250 x 160 x 58 mm

(WxDxH):

(WxDxH):

Dimensions of weighing plate

1190 x 840 x 90 mm

KERN UFB 1.5T0.5M





Level indicator: yes
Revolving screw feet: yes
Weighing surface (WxD): 1190 x 840 mm

Piktogramme

STANDARD CALEXTI CALEXTI DMS OPTIC DAkks +3 DAYS FACTO BT ACCU H3 DAYS ACCU H3 DAYS ACCU H3 DAYS

KERN UFB 600K200M

Pallet scale with steel load support (IP67) and EC type approval [M]





Measuring system	
Adjustment options:	External calibration
Eccentric loading at 1/3 [Max]:	400 g
Linearity:	400 g
Load cell connection:	4-wire
Readability [d]:	200 g
Recommended adjusting weight:	500 kg (M2)
Repeatability:	200 g
Resolution:	3000
Stabilisation time under laboratory conditions:	2s
Tare range:	-600 kg
Warm up time:	10 min
Weighing capacity [Max]:	600 kg
Weighing system:	Strain gauge
Weighing units:	kg

Display		
Display digit height (large):	5,200 cm	

Technical data about verification	
Minimum load [Min]:	4 kg
Periodic Verification for Italy:	969-112
Verification approval conforming to 2014/31/EU:	yes
Verification by KERN possible:	yes
Verification class:	III
Verification value [e]:	200 g

Functions		
Counting function:	yes	
Function to save totals:	yes	
Vibration-free weighing (Animal weighing program):	yes	
Weighing with tolerance range:	yes	
Environmental conditions		

Environmental conditions		
Maximum humidity:	95 %	
Maximum operating temperature:	40 °C	
Minimum ambient temperature:	-10 °C	
Minimum humidity:	10 %	
•		

Power supply	
Battery:	no battery
Charging time:	12 h
Input voltage:	100 V - 240 V 50 / 60 Hz
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	EURO CH UK
Operating time (Backlight off):	35 h
Operating time (Backlight on):	8 h
Rechargeable battery:	Rchrg. battery optional (factory)

Adjustment at the location of installation: 961-250		
DAkkS Certificate:	963-130	
Verification:	965-230	

Services (optional)

Dimensions of weighing plate

(WxDxH):

Category	
Brand:	KERN
Category:	Balances
Product Group:	Pallet scale

Floudel Gloup.	rallet scale
Packaging & shipping	
Delivery:	48 h
Dimensions packaging (WxDxH):	1420 x 910 x 310 mm
Gross weight:	87 kg
Net weight:	51 kg
Shipping method:	Freight forwarder
Construction	
Cable length:	5 m
Cable length of display device:	5 m
Dimensions of display device (WxDxH):	250 x 160 x 58 mm

1190 x 840 x 90 mm

KERN UFB 600K200M





Level indicator: yes

Revolving screw feet: yes

Weighing surface (WxD): 1190 x 840 mm

Piktogramme

