KERN ECB 10K-3N

Plain, mobile, uncomplicated





Measuring system	
Adjustment options:	External calibration
Eccentric loading at 1/3 [Max]:	15 g
Linearity:	20 g
Readability [d]:	5 g
Recommended adjusting weight:	5 kg (M3)
Repeatability:	5 g
Resolution:	2000
Stabilisation time under laboratory conditions:	2 s
Tare range:	10 kg
Warm up time:	10 min
Weighing capacity [Max]:	10 kg
Weighing system:	Strain gauge
Weighing units:	kg

Display

Display digit height (large): 2,100 cm

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	35 °C
Minimum ambient temperature:	5°C

Power supply	
Battery:	6x1.5 V AA
Charging time:	10 h
Input voltage:	220 V - 240 V AC 50 Hz
Mains adapter:	Mains adapter external
Operating time:	100 h
Operating time (Backlight off):	30 h
Operating time (Backlight on):	30 h
Rechargeable battery:	Rchrg. battery optional - intern

Services (optional)

Adjustment at the location of installation: 961-248

DAkkS Certificate: 963-128

Category

Brand: KERN
Category: Balances
Product Group: Bench scale

Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	380 x 405 x 90 mm
Gross weight:	2,880 kg
Net weight:	2,500 kg
Shipping method:	Parcel service

Construction

Casing material:	Plastic
Dimensions housing (WxDxH):	320 x 300 x 60 mm
Dimensions of weighing plate (WxDxH):	320 x 260 x 60 mm
Material weighing plate:	stainless steel
Weighing surface (WxD):	320 x 260 mm

Piktogramme

STANDARD



OPTION



KERN ECB 20K-2N

Plain, mobile, uncomplicated





Measuring system	
Adjustment options:	External calibration
Eccentric loading at 1/3 [Max]:	30 g
Linearity:	40 g
Readability [d]:	10 g
Recommended adjusting weight:	10 kg (M3)
Repeatability:	10 g
Resolution:	2000
Stabilisation time under laboratory conditions:	2 s
Tare range:	20 kg
Warm up time:	10 min
Weighing capacity [Max]:	20 kg
Weighing system:	Strain gauge
Weighing units:	kg

Display

Display digit height (large): 2,100 cm

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	35 °C
Minimum ambient temperature:	5°C

Power supply	
Battery:	6x1.5 V AA
Charging time:	10 h
Input voltage:	220 V - 240 V AC 50 Hz
Mains adapter:	Mains adapter external
Operating time:	100 h
Operating time (Backlight off):	30 h
Operating time (Backlight on):	30 h
Rechargeable battery:	Rchrg. battery optional - intern

Services (optional)

Adjustment at the location of installation: 961-248

DAkkS Certificate: 963-128

Category

Brand: KERN
Category: Balances
Product Group: Bench scale

Packaging & shipping

Delivery: 24 h

Dimensions packaging (WxDxH): 400 x 375 x 87 mm

Gross weight: 3 kg

Net weight: 2,500 kg

Shipping method: Parcel service

Construction

Casing material:

Dimensions housing (WxDxH):

Dimensions of weighing plate

(WxDxH):

Material weighing plate:

Weighing surface (WxD):

Plastic

320 x 300 x 60 mm

320 x 260 x 60 mm

320 x 260 x 60 mm

Piktogramme

STANDARD









OPTION



KERN ECB50K-2N

Plain, mobile, uncomplicated





Measuring system	
Adjustment options:	External calibration
Eccentric loading at 1/3 [Max]:	600 g
Linearity:	80 g
Readability [d]:	20 g
Recommended adjusting weight:	20 kg (M3)
Repeatability:	20 g
Resolution:	2500
Stabilisation time under laboratory conditions:	2 s
Tare range:	50 kg
Warm up time:	10 min
Weighing capacity [Max]:	50 kg
Weighing system:	Strain gauge
Weighing units:	kg

Display

Display digit height (large): 2,100 cm

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	35 °C
Minimum ambient temperature:	5°C

Power supply	
Battery:	6x1.5 V AA
Charging time:	10 h
Input voltage:	220 V - 240 V AC 50 Hz
Mains adapter:	Mains adapter external
Operating time:	100 h
Operating time (Backlight off):	30 h
Operating time (Backlight on):	30 h
Rechargeable battery:	Rchrg. battery optional - intern

Services (optional)

Adjustment at the location of installation: 961-248

DAkkS Certificate: 963-128

Category

Brand: **KERN** Category: Balances Product Group: Bench scale

Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	370 x 330 x 100 mm
Gross weight:	2,946 kg
Net weight:	2,500 kg
Shipping method:	Parcel service

Construction

Casing material:	Plastic
Dimensions housing (WxDxH):	320 x 300 x 60 mm
Dimensions of weighing plate (WxDxH):	320 x 260 x 60 mm
Material weighing plate:	stainless steel
Weighing surface (WxD):	320 x 260 mm

Piktogramme

STANDARD







OPTION

