

KERN CD10-3P1

Load cells made of stainless steel

KERN®



Construction

Cable length: 15 m

Piktogramme

STANDARD



Measuring system

| | |
|------------------------------------|---------|
| Combined Error: | 0,023 % |
| Load cell connection: | 4-wire |
| Nominal sensitivity: | 2 |
| OIML class: | C3 |
| Resolution Load cell à Verifiable: | 3000 e |
| Weighing capacity [Max]: | 10 t |
| Y value: | 10000 |

Environmental conditions

| | |
|--------------------------------|--------|
| Maximum operating temperature: | 65 °C |
| Maximum operating temperature: | 40 °C |
| Minimum ambient temperature: | -35 °C |
| Minimum operating temperature: | -10 °C |

Services (optional)

| | |
|--|----------|
| Factory calibration certificate (Pressure): | 961-266V |
|--|----------|

Category

| | |
|--------|--------|
| Brand: | Sauter |
|--------|--------|

Packaging & shipping

| | |
|-------------------------------|--------------------|
| Delivery: | 48 h |
| Dimensions packaging (WxDxH): | 220 x 220 x 160 mm |
| Gross weight: | 2,700 kg |
| Net weight: | 2,200 kg |
| Shipping method: | Parcel service |

KERN CD20-3P1

Load cells made of stainless steel

KERN[®]



Piktogramme

STANDARD



Measuring system

| | |
|------------------------------------|---------|
| Combined Error: | 0,023 % |
| Load cell connection: | 4-wire |
| Nominal sensitivity: | 2 |
| OIML class: | C3 |
| Resolution Load cell à Verifiable: | 3000 e |
| Weighing capacity [Max]: | 20 t |
| Y value: | 10000 |

Environmental conditions

| | |
|--------------------------------|--------|
| Maximum operating temperature: | 65 °C |
| Maximum operating temperature: | 40 °C |
| Minimum ambient temperature: | -35 °C |
| Minimum operating temperature: | -10 °C |

Category

| | |
|--------|--------|
| Brand: | Sauter |
|--------|--------|

Packaging & shipping

| | |
|-------------------------------|--------------------|
| Delivery: | 48 h |
| Dimensions packaging (WxDxH): | 220 x 220 x 160 mm |
| Gross weight: | 2,700 kg |
| Net weight: | 2,200 kg |
| Shipping method: | Parcel service |

Construction

| | |
|---------------|------|
| Cable length: | 15 m |
|---------------|------|

KERN CD40-3P1

Load cells made of stainless steel

KERN®



Piktogramme

STANDARD



Measuring system

| | |
|------------------------------------|---------|
| Combined Error: | 0,023 % |
| Load cell connection: | 4-wire |
| Nominal sensitivity: | 2 |
| OIML class: | C3 |
| Resolution Load cell à Verifiable: | 3000 e |
| Weighing capacity [Max]: | 40 t |
| Y value: | 10000 |

Environmental conditions

| | |
|--------------------------------|--------|
| Maximum operating temperature: | 65 °C |
| Maximum operating temperature: | 40 °C |
| Minimum ambient temperature: | -35 °C |
| Minimum operating temperature: | -10 °C |

Category

| | |
|--------|--------|
| Brand: | Sauter |
|--------|--------|

Packaging & shipping

| | |
|-------------------------------|--------------------|
| Delivery: | 48 h |
| Dimensions packaging (WxDxH): | 215 x 220 x 160 mm |
| Gross weight: | 3,200 kg |
| Net weight: | 2,706 kg |
| Shipping method: | Parcel service |

Construction

| | |
|---------------|------|
| Cable length: | 15 m |
|---------------|------|

KERN CD50-3P1

Load cells made of stainless steel

KERN®



Piktogramme

STANDARD



Measuring system

| | |
|------------------------------------|---------|
| Combined Error: | 0,023 % |
| Load cell connection: | 4-wire |
| Nominal sensitivity: | 2 |
| OIML class: | C3 |
| Resolution Load cell à Verifiable: | 3000 e |
| Weighing capacity [Max]: | 50 t |
| Y value: | 10000 |

Environmental conditions

| | |
|--------------------------------|--------|
| Maximum operating temperature: | 65 °C |
| Maximum operating temperature: | 40 °C |
| Minimum ambient temperature: | -35 °C |
| Minimum operating temperature: | -10 °C |

Category

| | |
|--------|--------|
| Brand: | Sauter |
|--------|--------|

Packaging & shipping

| | |
|-------------------------------|--------------------|
| Delivery: | 48 h |
| Dimensions packaging (WxDxH): | 215 x 220 x 160 mm |
| Gross weight: | 3,200 kg |
| Net weight: | 2,706 kg |
| Shipping method: | Parcel service |

Construction

| | |
|---------------|------|
| Cable length: | 15 m |
|---------------|------|