# KERN UFN1.5T0.5IPM



Pallet scale with stainless steel load support (IP67) and stainless steel display device (IP65), with EC type approval [M]



## Measuring system

<u> </u>	
Adjustment options:	External calibration
Eccentric loading at 1/3 [Max]:	500 g
Linearity:	500 g
Load cell connection:	4-wire
Readability [d]:	500 g
Recommended adjusting weight:	1500 kg (M1)
Repeatability:	500 g
Resolution:	3000
Stabilisation time under laboratory conditions:	3 s
Tare range:	-1,500 t
Warm up time:	10 min
Weighing capacity [Max]:	1,500 t
Weighing system:	Strain gauge
Weighing units:	kg

### Display

Display digit height (large):

5,200 cm

Technical	data about verification
ICOILINGAL	

Minimum load [Min]:	10 kg
Periodic Verification for Italy:	969-112
Verification approval conforming to 2014/31/EU:	yes
Verification by KERN possible:	yes
Verification class:	III
Verification value [e]:	500 g

Functions	
Counting function:	yes
Function to save totals:	yes
Vibration-free weighing (Animal weighing program):	yes
Weighing with tolerance range:	yes
Environmental conditions	
Maximum humidity:	95 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	10 %
Power supply	
Charging time:	10 h
Input voltage:	110 V - 230 V AC
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	UK EURO CH US
Operating time (Backlight off):	35 h
Operating time (Backlight on):	20 h
Services (optional)	
Adjustment at the location of installatio	n:961-250
DAkkS Certificate:	963-130
Verification:	965-230
Category	
outcyory	
Brand:	KERN
	KERN Balances
Brand:	
Brand: Category: Packaging & shipping	
Brand: Category:	Balances
Brand: Category: Packaging & shipping Delivery:	Balances 48 h
Brand: Category: Packaging & shipping Delivery: Dimensions packaging (WxDxH):	Balances 48 h 1410 x 910 x 210 mm
Brand: Category: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight:	Balances 48 h 1410 x 910 x 210 mm 85 kg
Brand: Category: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight:	Balances 48 h 1410 x 910 x 210 mm 85 kg 50 kg
Brand: Category: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method:	Balances 48 h 1410 x 910 x 210 mm 85 kg 50 kg Freight forwarder
Brand: Category: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: UN number:	Balances 48 h 1410 x 910 x 210 mm 85 kg 50 kg Freight forwarder
Brand: Category: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: UN number: Construction	Balances 48 h 1410 x 910 x 210 mm 85 kg 50 kg Freight forwarder 2800
Brand: Category: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: UN number: Construction Cable length:	Balances 48 h 1410 x 910 x 210 mm 85 kg 50 kg Freight forwarder 2800 5 m

# KERN UFN1.5T0.5IPM



Pallet scale with stainless steel load support (IP67) and stainless steel display device (IP65), with EC type approval [M]

Level indicator:	yes
Material weighing plate:	stainless steel
Revolving screw feet:	yes
Wall mount:	yes
Weighing surface (WxD):	1190 x 840 mm

## Piktogramme

### STANDARD



2 DAYS

OPTION

DAkks +3 days

#### FACTORY



# KERN UFN600K200IPM



Pallet scale with stainless steel load support (IP67) and stainless steel display device (IP65), with EC type approval [M]



## Measuring system

<b>3</b> - <b>3</b> - <b>3</b> - <b>3</b>	
Adjustment options:	External calibration
Eccentric loading at 1/3 [Max]:	200 g
Linearity:	200 g
Load cell connection:	4-wire
Readability [d]:	200 g
Recommended adjusting weight:	600 kg (M1)
Repeatability:	200 g
Resolution:	3000
Stabilisation time under laboratory conditions:	3 s
Tare range:	-600 kg
Warm up time:	10 min
Weighing capacity [Max]:	600 kg
Weighing system:	Strain gauge
Weighing units:	kg
Dianta	

#### Display

Display digit height (large):

5,200 cm

Technical data about verification	

Minimum load [Min]:	4 kg
Periodic Verification for Italy:	969-112
Verification approval conforming to 2014/31/EU:	yes
Verification by KERN possible:	yes
Verification class:	III
Verification value [e]:	200 g

Functions	
Counting function:	yes
Function to save totals:	yes
Vibration-free weighing (Animal weighing program):	yes
Weighing with tolerance range:	yes
Environmental conditions	
Maximum humidity:	95 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	10 %
Power supply	
Charging time:	10 h
Input voltage:	110 V - 230 V AC
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	UK EURO CH US
Operating time (Backlight off):	35 h
Operating time (Backlight on):	20 h
Services (optional)	
Adjustment at the location of installation	n:961-250
DAkkS Certificate:	963-130
Verification:	965-230
Category	
Brand:	KERN
Category:	Balances
Packaging & shipping	
Delivery:	48 h
Dimensions packaging (WxDxH):	1410 x 910 x 210 mm
Gross weight:	85 kg
Net weight:	55 kg
Shipping method:	Freight forwarder
UN number:	2800
Construction	
Cable length:	5 m
Cable length of display device:	5 m
Dimensions of display device (WxDxH):	267 x 173 x 93 mm
Dimensions of weighing plate (WxDxH):	1360 x 850 x 90 mm

# KERN UFN600K200IPM



Pallet scale with stainless steel load support (IP67) and stainless steel display device (IP65), with EC type approval [M]

Level indicator:	yes
Material weighing plate:	stainless steel
Revolving screw feet:	yes
Wall mount:	yes
Weighing surface (WxD):	1190 x 840 mm

## Piktogramme

### STANDARD



2 DAYS

OPTION

DAkks +3 days

#### FACTORY

