

# KERN CK1-0P1

Miniature load cells made of aluminium



## Measuring system

Combined Error:	0,030 %
Load cell connection:	4-wire
Nominal sensitivity:	1,500
OIML class:	C2
Weighing capacity [Max]:	1 kg

## Environmental conditions

Maximum operating temperature:	40 °C
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum operating temperature:	-10 °C

## Services (optional)

DAkkS Calibration certificate (Pressure):	963-261V
--	----------

## Category

Brand:	Sauter
--------	--------

## Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	145 x 60 x 35 mm
Gross weight:	55 g
Net weight:	12 g
Shipping method:	Parcel service

## Construction

Cable length:	25 cm
Dimensions (WxDxH):	80 x 10 x 12,7 mm

## Piktogramme

STANDARD



# KERN CK100-0P4

Miniature load cells made of aluminium



## Measuring system

Combined Error:	0,050 %
Load cell connection:	4-wire
Nominal sensitivity:	0,600
OIML class:	C1
Weighing capacity [Max]:	100 g

## Environmental conditions

Maximum operating temperature:	40 °C
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum operating temperature:	-10 °C

## Services (optional)

DAkkS Calibration certificate (Pressure):	963-261V
--	----------

## Category

Brand:	Sauter
--------	--------

## Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	145 x 60 x 35 mm
Gross weight:	370 g
Net weight:	10 g
Shipping method:	Parcel service

## Construction

Cable length:	25 cm
Dimensions (WxDxH):	47 x 20 x 6,6 mm

## Piktogramme

STANDARD



# KERN CK 1000-0P3

Miniature load cells made of aluminium



## Measuring system

Combined Error:	0,100 %
Load cell connection:	4-wire
Nominal sensitivity:	0,500
OIML class:	G10
Weighing capacity [Max]:	1 kg

## Environmental conditions

Maximum operating temperature:	40 °C
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum operating temperature:	-10 °C

## Services (optional)

DAkkS Calibration certificate (Pressure):	963-261V
--	----------

## Category

Brand:	Sauter
--------	--------

## Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	145 x 60 x 35 mm
Gross weight:	36 g
Net weight:	10 g
Shipping method:	Parcel service

## Construction

Cable length:	25 cm
Dimensions (WxDxH):	45,2 x 10,1 x 12,6 mm

## Piktogramme

### STANDARD



# KERN CK120-0P4

Miniature load cells made of aluminium



## Measuring system

Combined Error:	0,050 %
Load cell connection:	4-wire
Nominal sensitivity:	0,600
OIML class:	C1
Weighing capacity [Max]:	120 g

## Environmental conditions

Maximum operating temperature:	40 °C
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum operating temperature:	-10 °C

## Services (optional)

DAkkS Calibration certificate (Pressure):	963-261V
--	----------

## Category

Brand:	Sauter
--------	--------

## Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	145 x 60 x 35 mm
Gross weight:	370 g
Net weight:	10 g
Shipping method:	Parcel service

## Construction

Cable length:	25 cm
Dimensions (WxDxH):	47 x 20 x 6,6 mm

## Piktogramme

### STANDARD



# KERN CK2-0P1

Miniature load cells made of aluminium



## Measuring system

Combined Error:	0,030 %
Load cell connection:	4-wire
Nominal sensitivity:	1,200
OIML class:	C2
Weighing capacity [Max]:	2 kg

## Environmental conditions

Maximum operating temperature:	40 °C
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum operating temperature:	-10 °C

## Services (optional)

DAkkS Calibration certificate (Pressure):	963-261V
--	----------

## Category

Brand:	Sauter
--------	--------

## Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	145 x 60 x 35 mm
Gross weight:	55 g
Net weight:	12 g
Shipping method:	Parcel service

## Construction

Cable length:	25 cm
Dimensions (WxDxH):	80 x 10 x 12,7 mm

## Piktogramme

### STANDARD



# KERN CK3-0P1

Miniature load cells made of aluminium



## Measuring system

Combined Error:	0,030 %
Load cell connection:	4-wire
Nominal sensitivity:	1,200
OIML class:	C2
Weighing capacity [Max]:	3 kg

## Environmental conditions

Maximum operating temperature:	40 °C
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum operating temperature:	-10 °C

## Services (optional)

DAkkS Calibration certificate (Pressure):	963-261V
--	----------

## Category

Brand:	Sauter
--------	--------

## Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	145 x 60 x 35 mm
Gross weight:	55 g
Net weight:	12 g
Shipping method:	Parcel service

## Construction

Cable length:	25 cm
Dimensions (WxDxH):	80 x 12,7 x 12,7 mm

## Piktogramme

### STANDARD



# KERN CK300-0P2

Miniature load cells made of aluminium



## Measuring system

Combined Error:	0,030 %
Load cell connection:	4-wire
Nominal sensitivity:	1
OIML class:	C2
Weighing capacity [Max]:	300 g

## Environmental conditions

Maximum operating temperature:	40 °C
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum operating temperature:	-10 °C

## Services (optional)

DAkkS Calibration certificate (Pressure):	963-261V
--	----------

## Category

Brand:	Sauter
--------	--------

## Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	145 x 60 x 35 mm
Gross weight:	38 g
Net weight:	10 g
Shipping method:	Parcel service

## Construction

Cable length:	25 cm
Dimensions (WxDxH):	52 x 10 x 10 mm

## Piktogramme

STANDARD



# KERN CK300-0P4

Miniature load cells made of aluminium



## Measuring system

Combined Error:	0,050 %
Load cell connection:	4-wire
Nominal sensitivity:	0,900
OIML class:	C1
Weighing capacity [Max]:	300 g

## Environmental conditions

Maximum operating temperature:	40 °C
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum operating temperature:	-10 °C

## Services (optional)

DAkkS Calibration certificate (Pressure):	963-261V
--	----------

## Category

Brand:	Sauter
--------	--------

## Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	145 x 60 x 35 mm
Gross weight:	370 g
Net weight:	10 g
Shipping method:	Parcel service

## Construction

Cable length:	25 cm
Dimensions (WxDxH):	47 x 20 x 6,6 mm

## Piktogramme

STANDARD

