

Cleaning sets for microscopes KERN OCS-9





# Cleaning sets for microscopes

## **Features**

- This economical and fully equipped 7-piece cleaning set contains everything you need for the very best care of your microscope
- A silicon hand blower, dust brush, 60 ml of cleaning liquid, lint-free duster, optical cleaning cloths and cleaning swabs. You get all that in a high-quality KERN storage bag which you can also easily fix onto your belt
- You can use this set not only to gently clean your microscope, but also for example your camera, binoculars or all other optical surfaces

Model	Description	
KERN		
OCS 901	7-piece cleaning sets for microscopes und other optical instruments	



#### **Pictograms**



360° rotatable





Monocular Microscope

For the inspection with one eye



Binocular Microscope

For the inspection with both eyes



Trinocular Microscope

For the inspection with both eyes and the additional option for the connection of a camera



Abbe Condenser

With high numerical aperture for the concentration and the focusing of light



Halogen illumination

For pictures bright and rich in contrast



**LED** illumination

Cold, energy-saving and especially long-life illumination



Incident illumination

For non-transparent objects



Transmitting illumination

For transparent objects



Fluorescence illumination

For stereomicroscopes




Fluorescence illumination

for compound microscopes USB 2.0 With 100W mercury lamp and filter



Fluorescence illumination for compound microscopes

With 3 W LED illumination and filter



Phase contrast unit



Darkfield condenser/unit

For a higher contrast due to indirect illumination



Polarising unit

To polarise the light



Infinity system

Infinity corrected optical system



Zoom magnification For stereomicroscopes

**Auto-focus** 

For automatic control of the focus level



Parallel optical system

For stereomicroscopes, enables fatigue-proof working



Integrated scale

In the eyepiece



SD card

For data storage



USB 2.0 digital camera

For direct transmitting of the picture to a PC



USB 3.0 digital camera

For direct transmitting of the picture to a PC



WLAN data interface

For transmitting of the picture to a mobile display device



HDMI digital camera

For direct transmitting of the picture to a display



PC software

To transfer the measurements from the device to a PC



Automatic temperature compesation

For measurements between 10 °C and 30 °C



Protection against dust and water splashes

IPxx: The type of protection is shown in the pictogram cf. DIN EN 60529:2000-09, IEC 60529:1989+A1:1999+A2:2013



**Battery operation** 

Ready for battery operation. The battery type is specified for each device.



**Battery operation rechargeable** 

Prepared for a rechargeable battery operation



Plug-in power supply

230V/50Hz in standard version for EU. On request GB, AUS or USA version.



Integrated power supply unit

Integrated in microscope. 230V/50Hz standard EU. More standards e.g. GB, AUS or USA on request.



Package shipment

The time required to manufacture the product internally is shown in days in the pictogram.

## **Abbreviations**

Adapter for the connection of a C-Mount

Frames per second

camera to a trinocular microscope

LWD

N.A.

Long Working Distance

Numerical Aperture

SWF

Super Wide Field (Field number at least Ø 23 mm for 10× eyepiece)

W.D.

Working Distance

H(S)WF

**FPS** 

High (Super) Wide Field (Eyepiece with high eye point for wearers of glasses)

SLR camera Single-Lens Reflex camera

WF

Wide Field (Field number up to Ø 22 mm for 10× eyepiece)

### Your KERN specialist dealer: