


KERN CR 10000-1Q1

Load cells made of stainless steel

KERN®

Piktogramme

STANDARD



Measuring system

Combined Error:	0,050 %
Load cell connection:	4-wire
Nominal sensitivity:	2
OIML class:	C1
Resolution Load cell à Verifiable:	1000e
Weighing capacity [Max]:	10 t
Y value:	10000

Environmental conditions

Maximum operating temperature:	70 °C
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-50 °C
Minimum operating temperature:	-10 °C

Services (optional)

Factory calibration certificate (Pressure):	961-266V
--	----------

Category

Brand:	Sauter
--------	--------

Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	250 x 155 x 60 mm
Gross weight:	1,212 kg
Net weight:	1,100 kg
Shipping method:	Parcel service

Construction

Cable length:	10 m
---------------	------

KERN CR 20000-1Q1

Load cells made of stainless steel



Measuring system

Combined Error:	0,050 %
Load cell connection:	4-wire
Nominal sensitivity:	2
OIML class:	C1
Resolution Load cell à Verifiable:	1000e
Weighing capacity [Max]:	20 t
Y value:	10000

Environmental conditions

Maximum operating temperature:	70 °C
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-50 °C
Minimum operating temperature:	-10 °C

Category

Brand:	Sauter
--------	--------

Packaging & shipping


Delivery:	24 h
Dimensions packaging (WxDxH):	220 x 135 x 100 mm
Gross weight:	2,919 kg
Net weight:	2,800 kg
Shipping method:	Parcel service

Construction

Cable length:	10 m
---------------	------

Piktogramme

STANDARD




KERN CR 2500-1Q1

Load cells made of stainless steel

KERN®

Piktogramme

STANDARD



Measuring system

Combined Error:	0,050 %
Load cell connection:	4-wire
Nominal sensitivity:	2
OIML class:	C1
Resolution Load cell à Verifiable:	1000e
Weighing capacity [Max]:	2,500 t
Y value:	10000

Environmental conditions

Maximum operating temperature:	70 °C
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-50 °C
Minimum operating temperature:	-10 °C

Services (optional)

Factory calibration certificate (Pressure):	961-265V
---	----------

Category

Brand:	Sauter
--------	--------

Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	250 x 155 x 60 mm
Gross weight:	1,096 kg
Net weight:	1,050 kg
Shipping method:	Parcel service

Construction

Cable length:	10 m
---------------	------

KERN CR 30000-1Q1

Load cells made of stainless steel



Measuring system

Combined Error:	0,050 %
Load cell connection:	4-wire
Nominal sensitivity:	2
OIML class:	C1
Resolution Load cell à Verifiable:	1000e
Weighing capacity [Max]:	30 t
Y value:	10000

Environmental conditions

Maximum operating temperature:	70 °C
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-50 °C
Minimum operating temperature:	-10 °C

Category

Brand:	Sauter
--------	--------

Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	220 x 135 x 100 mm
Gross weight:	3,070 kg
Net weight:	2,800 kg
Shipping method:	Parcel service

Construction

Cable length:	10 m
---------------	------

Piktogramme

STANDARD



KERN CR 5000-1Q1

Load cells made of stainless steel

KERN®

Piktogramme

STANDARD



Measuring system

Combined Error:	0,050 %
Load cell connection:	4-wire
Nominal sensitivity:	2
OIML class:	C1
Resolution Load cell à Verifiable:	1000e
Weighing capacity [Max]:	5 t
Y value:	10000

Environmental conditions

Maximum operating temperature:	70 °C
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-50 °C
Minimum operating temperature:	-10 °C

Services (optional)

Factory calibration certificate (Pressure):	961-265V
--	----------

Category

Brand:	Sauter
--------	--------

Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	250 x 155 x 60 mm
Gross weight:	1,151 kg
Net weight:	1,100 kg
Shipping method:	Parcel service

Construction

Cable length:	10 m
---------------	------