

Price computing scale KERN RFE

NEW **PREMIUM**
★★★



Compact portion scale with 2 XXL displays – weight, unit price, total price and TARE value at a glance

Features

- Ideal as a salad scale, sweet scale, check-weigher, portion scale or zero-waste scale: Shopping without plastic or packaging waste in packaging-free supermarkets
- Large LCD display with four displays for weight display (verifiable), unit price, total price and stored TARE or PRE-TARE value
- TARE value display: this shows a TARE or PRE-TARE value stored in a PLU, which enables this value to be stored in a legally binding way in accordance with the Weights and Measures Act
- 1 Second display on the rear of the balance
- 2 Column to elevate the display as standard, can be easily fitted or removed by the user. The power cable for the second display can be stored in the folding column which is hygienic and gives a tidy appearance. Column height approx. 395 mm
- 3 Thanks to easily-understandable, universal symbols e.g. for weight, piece weight, total price this balance can also be understood and operated easily all over the world

- 4 Direct price keys for frequently recurring article prices
- Memory (PLU) for 100 article prices
- Article description can be entered, displayed and printed in plain text
- Unit price can be switched from EUR/kg to EUR/100 g
- Auto-clear-key: Unit price entry is automatically set to zero when scale is unloaded
- 3 Headers and footers of the printout can be programmed directly on the balance
- High mobility: thanks to rechargeable battery operation (optional), compact, lightweight construction, it is suitable for the use in several locations
- Recessed grips on the underside of the scale for easy transportation

Technical data

- Large backlit LCD display, digit height 20 mm
- Dimensions weighing surface, stainless steel, WxD 230x300 mm
- Overall dimensions WxDxH 320x450x130 mm
- Net weight approx. 4,2 kg
- Permissible ambient temperature -10 °C/40 °C

Accessories

- Label printer for printing weights on thermal labels, ASCII-capable, for further details, see Accessories, KERN YKE-01
- Rechargeable battery pack internal, operating time up to 60 h with backlight, charging time approx. 12 h, KERN GAB-A04

Application examples

- cafeterias, restaurants, Motorway service stations
- retail shops
- weekly markets
- farm shops
- pick your own fruit and vegetable sales

Note: Official verification is mandatory for commercial trade.

STANDARD							OPTION			FACTORY		

Model	Weighing capacity [Max] kg	Readability [d] g	Verification value [e] g	Minimal load [Min] g	Option		
					Verification KERN	DAkkS Calibr. Certificate DAkkS KERN	
Dual-range balance switches automatically to the next largest weighing capacity [Max] and readability [d]							
RFE 6K3M	3 6	1 2	1 2	20	965-228		963-128
RFE 15K3M	6 15	2 5	2 5	40	965-228		963-128
RFE 30K3M	15 30	5 10	5 10	100	965-228		963-128

Note: For applications that require verification, please order verification at the same time, initial verification at a later date is not possible. Verification at the factory, we need to know the full address of the location of use.

Pictograms

Internal adjusting: Quick setting up of the balance's accuracy with internal adjusting weight (motordriven)	KERN Communication Protocol (KCP): It is a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems	Suspended weighing: Load support with hook on the underside of the balance
Adjusting program CAL: For quick setting up of the balance's accuracy. External adjusting weight required	GLP/ISO log: The balance displays serial number, user ID, weight, date and time, regardless of a printer connection	Battery operation: Ready for battery operation. The battery type is specified for each device
Easy Touch: Suitable for the connection, data transmission and control through PC or tablet.	GLP/ISO log: With weight, date and time. Only with KERN printers.	Rechargeable battery pack: Rechargeable set
Memory: Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.	Piece counting: Reference quantities selectable. Display can be switched from piece to weight	Universal plug-in power supply: with universal input and optional input socket adapters for A) EU, CH, GB; B) EU, CH, GB, USA; C) EU, CH, GB, USA, AUS
Alibi memory: Secure, electronic archiving of weighing results, complying with the 2014/31/EU standard.	Recipe level A: The weights of the recipe ingredients can be added together and the total weight of the recipe can be printed out	Plug-in power supply: 230V/50Hz in standard version for EU, CH. On request GB, USA or AUS version available
Data interface RS-232: To connect the balance to a printer, PC or network	Recipe level B: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display	Integrated power supply unit: Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request
RS-485 data interface: To connect the balance to a printer, PC or other peripherals. Suitable for datatransfer over large distances. Network in bus topology is possible	Totalising level A: The weights of similar items can be added together and the total can be printed out	Weighing principle: Strain gauges: Electrical resistor on an elastic deforming body
USB data interface: To connect the balance to a printer, PC or other peripherals	Percentage determination: Determining the deviation in % from the target value (100 %)	Weighing principle: Tuning fork: A resonating body is electromagnetically excited, causing it to oscillate
Bluetooth* data interface: To transfer data from the balance to a printer, PC or other peripherals	Weighing units: Can be switched to e.g. nonmetric units. See balance model. Please refer to KERN's website for more details	Weighing principle: Electromagnetic force compensation: Coil inside a permanent magnet. For the most accurate weighings
WiFi data interface: To transfer data from the balance to a printer, PC or other peripherals	Weighing with tolerance range: (Checkweighing) Upper and lower limiting can be programmed individually, e.g. for sorting and dosing. The process is supported by an audible or visual signal, see the relevant model	Weighing principle: Single cell technology: Advanced version of the force compensation principle with the highest level of precision
Control outputs (optocoupler, digital I/O): To connect relays, signal lamps, valves, etc.	Hold function: (Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value	Verification possible: The time required for verification is specified in the pictogram
Analogue interface: to connect a suitable peripheral device for analogue processing of the measurements	Protection against dust and water splashes IPxx: The type of protection is shown in the pictogram.	DAKkS calibration possible (DKD): The time required for DAKkS calibration is shown in days in the pictogram
Interface for second balance: For direct connection of a second balance		Factory calibration (ISO): The time required for Factory calibration is shown in days in the pictogram
Network interface: For connecting the scale to an Ethernet network		Package shipment: The time required for internal shipping preparations is shown in days in the pictogram
		Pallet shipment: The time required for internal shipping preparations is shown in days in the pictogram

*The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by KERN & SOHN GmbH is under license. Other trademarks and trade names are those of their respective owners.

KERN – Precision is our business

To ensure the high precision of your balance KERN offers you the the appropriate test weight in the international OIML error limit classes E1-M3 from 1 mg - 2500 kg. In combination with a DAKkS calibration certificate the best pre-requisite for proper balance calibration.

The KERN DAKkS calibration laboratory today is one of the most modern and best-equipped DAKkS calibration laboratories for balances, test weights and force-measurement in Europe.

Thanks to the high level of automation, we can carry out DAKkS calibration of balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

Range of services:

- DAKkS calibration of balances with a maximum load of up to 50 t
- DAKkS calibration of weights in the range of 1 mg - 2500 kg
- Volume determination and measuring of magnetic susceptibility (magnetic characteristics) for test weights
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DAKkS calibration certificates in the following languages DE, EN, FR, IT, ES, NL, PL
- Conformity evaluation and reverification of balances and test weights

Your KERN specialist dealer: